

SXM 4

4th International Conference on the Development and Technological Application of Scanning Probe Methods

Infiltrated Carbon Fiber Felts Investigated by AFM

A. Pfrang¹, H. Gliemann² and Th. Schimmel^{1,2}

¹Institute of Applied Physics, Universität Karlsruhe, D-76128 Karlsruhe, Germany

²Institute of Nanotechnology, Forschungszentrum Karlsruhe, D-76344 Eggenstein-Leopoldshafen, Germany

Due to their mechanical and thermal properties and their low specific weight, carbon fiber felts infiltrated with pyrolytic carbon are suited for a variety of technical applications in the high temperature regime. Therefore, a thorough understanding of the relationship between these properties and the infiltration parameters is of great interest.

A combination of atomic force microscopy including lateral force microscopy (LFM) and force modulation microscopy (FMM) with pulsed force mode (PFM) operation was applied to investigate the surface structure, elasticity, adhesion and lateral forces of infiltrated carbon fiber felts and infiltrated carbon fiber bundles.

A clear material contrast between fibers and matrix was observed in LFM as well as in FMM and PFM, and three different microstructures of carbon in the matrix could be distinguished: isotropic (or dark laminar), smooth laminar and rough laminar pyrolytic carbon. AFM also allowed to study the spreading of microcracks in the region of the fiber matrix interface. The AFM results were compared with polarized light micrographs.

Preferred Presentation: *Poster*

Titel: *Infiltrated carbon fiber felts investigated by AFM*

Workshop: *5. Scanning Force Microscopy for the Measurement of Mechanical Properties*